

## Quad 2.5" HDD / SSD Bracket with Tool-less Drive Installation for 5.25" Bay



Weidenweg 21H 47059 Duisburg, Germany Email: support@icydock.com





Package Contents • Packungsinhalt • Contenu • Contenido del paquete いて●包裝說明 ● 包装说明



Bracket






8 x M3\*6 Pan Head Screw for Bracket

(Optional) 3 x M2.5\*7 Flat Head Screw for Organizing Rack


Installation Guide • Installationsanleitung • Guide d'Installation • Guía de instalación ● 製品の組み込み手順について ● 操作步驟 ● 操作步骤


1. Installing 2.5" HDD/SSD - Insert the 2.5" HDD/SSD until an audible 'click' indicates that the drive is installed securely.






2. Removing 2.5" HDD/SSD - Simply eject the HDD/SSD by pressing the drive eject button and then pull out the drive.





Copyright © ICY DOCK International, All Rights Reserved, 6502302 VER 3.0

3. Device Installation - Use the included four screws to mount the FLEX-Fit Quattro into a 5.25" device bay with two screws on each side. Connect the power and data connectors to the installed drives to complete device installation.



## (Optional) Use FLEX-FIT Quattro as 2.5" HDD / SSD storage organizing rack


Flex-Fit Quattro can be used as a storage organizing rack. In addition, it can be expanded by stacking additional bracket on top of each other. (see below)

1. Two brackets are required to perform this installation.






2. Remove the pre-installed 3 x M2.5\*7 screws from Set B to split into two bracket layers (B-1 & B-2). Please keep the removed 3 x M2.5\*7 screws for installing bracket layers onto Set A)



3. Use 3 x M2.5\*7 screws to install B-1 onto Set A. To add more layers, simply place another bracket layer on top and secure it with 3 x M2.5\*7 screws.





ICY DOCK reserves the right to change product specifications, components, or accessories without prior notice. For the warranty information, please visit www.icydock.com/warranty.php